

## Aluminum Hydraulic Shores\*

**Vertical Rail Length: Rails: 2'-1 Ram | 3.5', 5', 7'- 2 Ram | 9', 12', - 3 Ram | 16' - 4 Ram**

Model No.	Trench Width Min. – Max.	Model No.	Trench Width Min. – Max.
1727	1' 5" – 2' 3"	79-115	6'7" – 9'7"
2236	1'10" – 3'0"	88-124	7'4" – 10'4"
2542	2'1" – 3'6"	94-130	7'10" – 10'10"
2846	2'4" – 3'10"	97-133	8'1" – 11'1"
3145	2'7" – 3'9"	106-142	8'10" – 11'10"
3456	2'10" – 4'8"	108-144	9'0" – 12'0"
4064	3'4" – 5'4"	124-160	10'4" – 13'4"
5288	4'4" – 7'4"	132-168	11'0" – 14'0"
6197	5'1" – 8'1"	144-180	12'0" – 15'0"
70-106	5'10" – 8'10"	162-198	13'6" – 16'6"
76-112	6'4" – 9'4"	180-216	15'0" – 18'0"

## End Shores\*

**Rail Lengths: 2' – 1 Ram / 5', 6', 7', 8' – 2 Ram**

Model No.	Trench Width Min - Max	Model No.	Trench Width Min - Max
2640	2'5" – 3'7"	73109	6'4" – 9'4"
3250	2'11" – 4'5"	79115	6'10" – 9'10"
3859	3'5" – 5'2"	94130	8'1" – 11'1"
4468	3'11" – 5'11"	108144	9'3" – 12'0"
5692	4'11" – 7'11"		

\*Prior to use, refer to OSHA's 29 CFR, Part 1926 (subpart P) and Manufacturers Tabulated Data for detailed explanation of soil types and product application.

Type A soil not to exceed 25 PSF per foot of depth; Type B soil not to exceed 45 PSF per foot of depth; Type C (60) soil not to exceed 60 PSF per foot of depth; Type C soil not to exceed 80 PSF per foot of depth. (PSF = Pounds per Square Foot)



"Commitment To Safety & Service"  
Since 1973

[TrenchShoring.com](http://TrenchShoring.com)

<b>Compton</b>	<b>310-327-5554</b>
<b>Bakersfield</b>	<b>661-396-9160</b>
<b>Banning</b>	<b>951-849-1611</b>
<b>Corona</b>	<b>951-734-4290</b>
<b>Fresno</b>	<b>559-691-4123</b>
<b>Fullerton</b>	<b>714-879-1005</b>
<b>Lake Forest</b>	<b>949-454-0858</b>
<b>Moorpark</b>	<b>805-529-4614</b>
<b>San Diego</b>	<b>858-530-2500</b>
<b>San Leandro</b>	<b>510-900-0595</b>
<b>Las Vegas</b>	<b>702-651-0920</b>